



Lubricants



Aerospace Approval



MOD Approval



High temperature resistant

AMS4 SILICONE GREASE

MULTI-PURPOSE SILICONE GREASE

Ambergrease AMS4 is an inert, military & aviation grade XG250 silicone grease for use on rubber seals to prevent cracking, on 3-phase connectors to prevent moisture ingress and for general lubrication.

AMS4 Silicone Grease provides a smooth, non-melting coating with a broad spectrum of applications. Meets military and aviation specifications.

PRODUCT CODES / FILL SIZES



31566 / 400ml

APPLICATIONS

- Electronics and Telecommunications: insulates high voltage parts against leaking and arcing; protects switch gear against oxidation; waterproofs components in damp or humid conditions.
- Transport: lubricates door strips, door runners and curtain side tracks; prevents freezing of locks; preserves seals against cracking and hardening.
- Aviation: seals exposed components against moisture ingress; helps to prevent ice build-up.
- Mechanical, Engineering and Production: lubricates slow running gears, metal to metal surfaces and other moving parts; assists assembly of tight fitting components (e.g. installation of cables through conduits); prevents seizing on connections and fittings; aids release of epoxy resin and other types of plastic mouldings.

DIRECTIONS

- Shake the can well before each use.
- Hold in an upright position and apply a light even coating from approximately 10 – 15 cm.

TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Cloudy white liquid
Odour	Hydrocarbon solvent
SG @ 25°C	0.81
Pressure @ 25°C	3.4 Bar
Discharge rate	0.8 g/sec
Temperature range	-50°C to +200°C
Solubility	Soluble in most solvents, insoluble in water
Flammability	Classified as extremely flammable under current EC Regulations
NLGI Grade	NLGI 3
Specifications / Approvals	Formulated using grease which conforms to Def. Stan 68-69/1(Grease XG-250, NATO Code S-736) and to MIL-S-8660B, Nato Stock No. 5970-99-224-4975, Service Management Code. RAF-34B

MATERIALS COMPATIBILITY (BASE GREASE)

OK	All metals, PETG, PTFE, crosslinked polyethylene, ECTFE and PVDF, Buna/Nitrile, EPDM, Butyl, PMP, Natural rubber, Viton, POM, HDPE, LDPE, Nylon (PA) and PP
CAUTION	Prior to application, users should conduct their own tests to ensure suitability & materials compatibility
NOT OK	Silicone Rubber

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 2.1
Created: August 2018
Updated: N/A

CRC Industries UK Ltd.
Wylds Road, Bridgwater
Somerset, TA6 4DD
United Kingdom

t +44 (0)1278 727200
f +44 (0)1278 425644
e sales.uk@crcind.com
w www.ambersil.com

Company Registered No. 04910479

VAT No. GB 821 5195 42

